

CLAIMS:

sub. A2
add C17

1. A catalyst warming control apparatus for a hybrid vehicle having an internal combustion engine, a generator for generating electric power from the output from the internal combustion engine, a power storage unit for storing electric power generated by the generator, and an electric motor driven by the electric power stored in the power storage unit, the hybrid vehicle being driven by at least one of the outputs from the internal combustion engine and the motor, the catalyst warming control apparatus comprising:

a temperature detector for detecting the temperature of a catalyst or a value relating to the same;

a first comparison circuit for comparing the detected result from the temperature detector with a preset reference value; and

a control circuit for allowing the generator to generate electric power and to store the power in the power storage unit when the internal combustion engine is driven, and when the detected result by the temperature detector is equal to or below the reference value according to the output from the comparison circuit.

Sub B1

2. A catalyst warming control apparatus according to claim 1, further comprising:

a remaining charge detector for detecting a remaining charge of the

claim 2 is OK

09643912-082300

power storage unit or a value relating to the
a second comparison circuit for comp
the remaining charge detector with a preset
remaining charge, wherein

a second comparison circuit for comparing the detected result from the remaining charge detector with a preset ^{second} reference value relating to the remaining charge, wherein

the control circuit drives the vehicle by the output from the internal combustion engine, and allows the generator to generate electric power and to store the power in the power storage unit, when the detected result from

X the temperature detector is equal to or below the ^{first} reference value according to the output from the first comparison circuit, and when the detected result

X from the remaining charge/detector is equal to or below the ^{second} reference value relating to the remaining charge according to the output from the second comparison circuit.

3. A catalyst warming control apparatus according to claim 1, further comprising:

a remaining charge detector for detecting a remaining charge of the power storage unit or a value relating to the same; and

a second comparison circuit for comparing the detected result from the remaining charge detector with a preset reference value relating to the remaining charge, wherein

the control circuit allows the generator to generate electric power, and drives the vehicle by the generated electric power and the stored electric power, when the detected result from the temperature detector is equal to or

reference value according to the detected residual value when the detected residual value is less than the reference value relating to the second comparison. The catalyst warming control circuit allows the generator to be driven by the motor, when the detected residual value is equal to or below the reference value relating to the comparison circuit, and when the battery charge detector is above the reference value relating to the charge according to the detected residual value.

- X

X

add
D'